

### DIRECTIONS TO THE SITE

FROM THE T-MOBILE OFFICE IN ATLANTA, GEORGIA: TAKE HEAD NORTH ON CONCOURSE PKWY NE AND TURN RIGHT TOWARD HAMMOND DR NE. TURN LEFT ONTO HAMMOND DR NE AND TURN RIGHT ONTO THE GEORGIA 400 N RAMP AND MERGE ONTO US-19 N AND TAKE EXIT 6 FOR NORTHRIDGE RD. TURN SLIGHT RIGHT ONTO NORTHRIDGE RD AND TAKE THE 1ST RIGHT ONTO DUNWOODY PL. TURN RIGHT ONTO ROSWELL RD AND CONTINUE ONTO S ATLANTA ST. TURN LEFT ONTO GA-120 W AND TURN RIGHT ONTO WILLED RD. TURN RIGHT ONTO COLEMAN RD AND TAKE THE 2ND LEFT ONTO HIGHTOWER RD. THE DESTINATION WILL BE ON

# South, LLC

# **WILLEO CREEK 2** 9AT0289B SITE MODERNIZATION

9870 HIGHTOWER ROAD **ROSWELL, GA 30075** 

E-2

### SITE SUMMARY

SITE TYPE:

SITE MODERNIZATION

TOWER TYPE:

WATER TANK

TOWER LATITUDE:

34° 01' 16.01" (NAD 83) 84° 23' 05.08" (NAD 83)

TOWER LONGITUDE: ZONING JURISDICTION:

CITY OF ROSWELL

E2

ZONING CLASSIFICATION:

PARCEL TAX I.D.:

LOT#266, 1ST DISTRICT

### OCCUPANCY NOTE:

THIS FACILITY IS AN UNOCCUPIED TELECOMMUNICATIONS SWITCH THAT WILL ONLY BE OCCUPIED FOR BRIEF INTERVALS WHEN MAINTENANCE OR EQUIPMENT UPGRADES ARE REQUIRED. ONCE CONSTRUCTION AND FULLY OPERATIONAL. THE FACILITY WILL BE OCCUPIED FOR LESS THAN 8 HOURS AT A TIME. SANITARY SEWER IS NOT REQUIRED.

### SITE SUMMARY NOTE:

INFORMATION SHOWN IN THIS SECTION WAS PROVIDED BY OTHERS AND HAS NOT BEEN VERIFIED BY COMPASS.

### HANDICAP REQUIREMENTS:

FACILITY IS UNMANNED AND NOT FOR HUMAN HABITATION. HANDICAP ACCESS IS NOT REQUIRED.

PLUMBING REQUIREMENTS:

FACILITY HAS NO SANITARY OR POTABLE WATER.

### PROJECT DIRECTORY

APPLICANT: T-MOBILE SOUTH, LLC ONE RAVINIA DRIVE

SUITE 1000

ATLANTA, GA 30346 CONTACT: KIMBERLY ADAMS

(404) 226-8915

SITE DESIGN: COMPASS TECHNOLOGY SERVICES 5449 BELLS FERRY ROAD

ACWORTH, GEORGIA 30102

DESIGN MANAGER: JOHN CUNNINGHAM (770) 701-2500 EXT. 141

OWNER:

CITY OF ROSWELL 38 HILL STREET

ROSWELL, GA 30075 CONTACT: CITY ADMINISTRATOR

TEL: 770-209-7979

UNDERGROUND CALL TOLL FREE 1-800-282-7411

THREE WORKING DAYS BEFORE YOU DIG

## SHEET INDEX SITE SPECIFIC SHEETS

PLUMBING DIAGRAM


09/04/12 TITLE SHEET T-1C-108/27/12 COMPOUND PLAN C-2EQUIPMENT PLANS 08/27/12 S - 1TOWER ELEVATION & ANTENNA ORIENTATION 08/27/12 09/04/12 S-2ANTENNA & COAXIAL CABLE SCHEDULE 08/27/12 S-3ANTENNA MOUNT DETAIL 08/27/12 E-1GENERAL ELECTRICAL NOTES & SYMBOLS


REV.

DATE

SIGNATURE DATE PROPERTY/ TOWER OWNER SIGNATURE DATE SITE ACQUISISTION MANAGER SIGNATURE DATE CONSTRUCTION MANAGER SIGNATURE DATE RF ENGINEER

DEVELOPMENT MANAGER







9AT0289B

WILLEO CREEK 2

APPROVED BY:

M. PRATHER DESIGNED BY: T MERCHANT PROJECT NO: 100396


TITLE SHEET


THE CONTRACTOR SHALL VISIT THE SITE BEFORE BIDDING

ON THE WORK CONTAINED WITHIN THIS DESIGN PACKAGE. DISCREPANCIES AND OMISSIONS SHALL BE BROUGHT TO THE ENGINEER'S ATTENTION PRIOR TO BIDDING.

### NOTES:


- CONTRACTOR TO FIELD COORDINATE EXACT LOCATION OF PROPOSED COVP AND OPTIONAL FIBER EXCESS BOX WITH EXISTING CONDITIONS ON SITE.
- 2. PROPOSED EQUIPMENT SHALL BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS.





NOTE:

THIS SITE DESIGN HAS BEEN PREPARED WITHOUT THE BENEFIT OF AN AS-BUILT SURVEY. SLIGHT VARIATIONS MAY EXIST BETWEEN THIS SITE PLAN AND TRUE DIMENSIONS IN THE FIELD. THE CONTRACTOR SHALL VERIFY EXISTING CONDITIONS.



5449 Bells Ferry Road Acworth, Georgia 30102 770-701-2500 Fax 770-701-2501

WALTER MATHEWS PRATHER, P.E. GEORGIA P.E. No. 19114

08/27/12 ISSUED FOR

07/30/12 ISSUED FOR N

0 07/02/12 ISSUED FOR T CONSTRUCTION

NO. DATE REVISIONS

NOT VALID WITHOUT SIGNATURE AND D



PREPARED FOR



SITE NUMBER

9AT0289B

WILLEO CREEK 2

PREPARED BY -

 APPROVED BY:
 M. PRATHER

 DESIGNED BY:
 T. MERCHANT

 PROJECT NO:
 100396

 DATE:
 05/30/12


IEET NAME -


SITE PLAN AND NOTES

SHEET NUMBE

C-1

compass






### NOTES:

- CONTRACTOR TO FIELD COORDINATE EXACT LOCATION OF PROPOSED FXFB, FRIG AND COVP UNITS WITH EXISTING CONDITIONS
- 2. PROPOSED EQUIPMENT SHALL BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS. ALL HARDWARE FASTENERS SHALL BE HIGH STRENGTH (A325, A36).
  DRILLING OF EXISTING STEEL MEMBERS IS NOT PERMITTED.
- 4. BOND PROPOSED EQUIPMENT TO EXISTING SECTOR GROUND BAR PER MANUFACTURER'S SPECIFICATIONS. PROVIDE ADDITIONAL SECTOR GROUND BARS AS REQUIRED.
- ALL ANTENNAS, CABLES, AND MOUNTS SHALL BE INSTALLED IN ACCORDANCE WITH THE TOWER ENGINEER'S RECOMMENDATIONS IN A MANNER CONSISTENT WITH THE STRUCTUR ANALYSIS REPORT.

  THIS ANTENNA ORIENTATION PLAN IS SCHEMATIC. THE CONTRACTOR SHALL VERIFY TOWER ORIENTATION AND FIELD COORDINATE REQUIRED ADJUSTMENTS TO ACHIEVE THE DESIRED ANTENNA AZIMUTHS.
- TOWER STRUCTURAL ANALYSIS BY OTHERS.
- CONTRACTOR TO CONTACT T-MOBILE FOR UP-TO-DATE RF DESIGN DATA. NOTIFY ENGINEER IF CONFLICT EXISTS.
- HYBRID CABLE LENGTH FROM OVP TO RRU SHALL NOT EXCEED 15'.
- 10. COAX JUMPER LENGTH FROM RRU TO ANTENNA SHALL NOT EXCEED 15'.



9AT0289B

WILLEO CREEK 2

DESIGNED BY: T. MERCHANT

PROJECT NO: 100396 05/30/12

TOWER ELEVATION & ANTENNA INFORMATION

S-1

ANTENNA SECTOR	ANTENNA MARK	ANTENNA MODEL	ANTENNA AZIMUTH	RRU MODEL	TMA MODEL	TOWER TOP COVP MODEL	ANTENNA CABLE DESCRIPTION
ALPHA	A3	(1) RFS APX17DWVS - (P)	30*	(1) FRIG - (P)	-		_
	A2	(1) RFS APXV18-206517S-C - (E)	30°	-	(1) RFS ATMAA 1412D-1A20 - (E)	(1) TOP COVP – (P)	(1) 1.24" x 175 LF LOW CAPACITY HYBRID CABLE - (P) (2) 1-5/8" DIA. U2100 COAX CABLE - (E)
	A1	(1) RFS APX17DWVS - (P)	30*	(1) FXFB - (P)	-		(2) 1-5/8" DIA. E911 COAX CABLE - (E)
BETA	B3	(1) RFS APX17DWVS - (P)	160*	(1) FRIG - (P)	-	(1) TOP COVP - (P)	-
	B2	(1) RFS APXV18-206517S-C - (E)	160*	-	(1) RFS ATMAA 1412D-1A20 - (E)		(1) 1.24" × 200 LF LOW CAPACITY HYBRID CABLE - (P) (2) 1-5/8" DIA. U2100 COAX CABLE - (E)
	B1	(1) RFS APX17DWVS - (P)	160*	(1) FXFB - (P)	-		(2) 1-5/8" DIA. E911 COAX CABLE - (E)
GAMMA	C3	(1) RFS APX17DWVS - (P)	290*	(1) FRIG - (P)	-		-
	C2	(1) RFS APXV18-206517S-C - (E)	290	_	(1) RFS ATMAA 1412D-1A20 - (E)	(1) TOP COVP - (P)	(1) 1.24" x 250 LF LOW CAPACITY HYBRID CABLE - (P) (2) 1-5/8" DIA. U2100 COAX CABLE - (E)
	C1	(1) RFS APX17DWVS - (P)	290°	(1) FXFB - (P)	-		(2) 1-5/8" DIA. E911 COAX CABLE - (E)

### EQUIPMENT NOTES:

- THE HYBRID CABLE LENGTH SHOW IS ONLY AN ESTIMATE AND SHOULD NOT BE USED FOR ORDERING MATERIALS. CONFIRM THE REQUIRED HYBRID CABLE LENGTH WITH T-MOBILE PRIOR TO ORDERING OR INSTALLATION.
- 2. THE CONTRACTOR SHALL TEST THE OPTICAL FIBER AFTER INSTALLATION IN ACCORDANCE WITH T-MOBILE STANDARDS AND SUPPLY THE RESULTS TO T-MOBILE.
- 3. THE CONTRACTOR SHALL CONFIRM THE TOWER TOP EQUIPMENT LIST ABOVE WITH THE FINAL T-MOBILE RFDS PRIOR TO INSTALLATION.
- 4. ALL EXISTING AND PROPOSED ANTENNA CABLES SHALL BE COLOR CODED PER T-MOBILE STANDARDS.
- 5. REFER TO NOKIA SIEMENS NETWORKS EQUIPMENT INSTALLATION STANDARDS FOR ADDITIONAL INFORMATION.
- 6. REFER TO EQUIPMENT MANUFACTURER'S SPECIFICATION SHEETS FOR ADDITIONAL INFORMATION NOT LISTED ABOVE.

2A_U2100	2A_U2100 ON GROUND TOWER LOADING SUMMARY						
EQUIPMENT Type	EXISTING QUANTITY	REMOVE QUANTITY	ADD QUANTITY	TOTAL QUANTITY			
PANEL ANTENNA	9	6	6	9			
COAX CABLE	18	6	0	12			
TMA	9	6	0	3			
FRIA/E	0	0	0	0			
FRIG	0	0	3	3			
FXFB	0	0	3	3			
HYBRID CABLE	0	0	3	3			
TOP COVP	0	0	3	3			
BOTTOM COVP	0	0	1	1			

1 ANTENNA & COAXIAL CABLE SCHEDULE SCALE: N/A



5449 Bells Ferry Road Acworth, Georgia 30102 770-701-2500 Fax 770-701-2501 WALTER MATHEWS PRATHER, P.E. GEORGIA P.E. No. 19114

3 09/04/12 ISSUED FOR CONSTRUCTION

2 08/27/12 ISSUED FOR CONSTRUCTION

1 07/30/12 ISSUED FOR CONSTRUCTION

1 07/30/12 ISSUED FOR CONSTRUCTION

0 07/02/12 ISSUED FOR CONSTRUCTION

NO. DATE REVISIONS BY

NOT VALID WITHOUT SIGNATURE AND DAT



ONE RAVINIA DRIVE : SUITE 1000
ATLANTA, GEORGIA 30346
PHONE: (770) 630-8980
FAX: (770) 350-3049

SITE NUMBER -

-----

WILLEO CREEK 2

9AT0289B

PREPARED BY M. PRATHER

DESIGNED BY: T. MERCHANT
PROJECT NO: 100396

DATE: 05/30/12


ANTENNA & COAXIAL CABLE SCHEDULE

SHEET NUMBER -

S-2

### NOTES:


- ALL COMPONENTS AND HARDWARE SHALL BE OF A SUITABLE MATERIAL OR TREATED TO RESIST CORROSION.
- 2. SEAL AROUND ALL PENETRATIONS WITH A UL LISTED SILICONE SEALANT.



ANTENNA MOUNT DETAIL SCALE: NOT TO SCALE



THIS SITE DESIGN HAS BEEN PREPARED WITHOUT THE BENEFIT OF AN AS-BUILT SURVEY. THE INFORMATION SHOWN IS NOT BASED ON AN ACTUAL FIELD SURVEY. THE CONTRACTOR SHALL VERIFY EXISTING CONDITIONS.



5449 Bells Ferry Road Acworth, Georgia 30102 770-701-2500 Fax 770-701-2501 WALTER MATHEWS PRATHER, P.E. GEORGIA P.E. No. 19114

DESIGN	REVISIONS .

2 08/27/12

08/13/12 ISSUED FOR CONSTRUCTION

0 07/02/12 ISSUED FOR CONSTRUCTION

NO. DATE NOT VALID WITHOUT SIGNATURE AND DAT





9AT0289B

WILLEO CREEK 2

APPROVED BY: T. MERCHANT DESIGNED BY: PROJECT NO: 100396 05/30/12

ANTENNA MOUNT DETAIL

### **GENERAL ELECTRICAL NOTES:**

- 1. SCOPE: PROVIDE LABOR, MATERIALS, AND EQUIPMENT, ETC., REQUIRED TO COMPLETE THE INSTALLATION SHOWN ON THE DRAWINGS.
- 2. CODES AND STANDARDS: INSTALLATION SHALL COMPLY WITH APPLICABLE LAWS AND ORDINANCES, UTILITY COMPANY REGULATIONS, AND APPLICABLE REQUIREMENTS OF LATEST EDITIONS OF:
  - A. NFC NATIONAL FIRE CODES
  - B. UL UNDERWRITERS LABORATORIES
  - NEC NATIONAL ELECTRICAL CODE
  - NEMA NATIONAL ELECTRIC MANUFACTURERS ASSOCIATION
  - OSHA OCCUPATIONAL SAFETY AND HEALTH ACT
- SBC STANDARD BUILDING CODE
- 3. PERMITS: OBTAIN AND PAY FOR REQUIRED PERMITS, LICENSES, FEES, INSPECTIONS, ETC.
- 4. COORDINATION: COORDINATE WORK WITH OTHER TRADES.
- 5. SUBMITTALS: SUBMIT BROCHURES FOR APPROVAL ON SERVICE DISCONNECTING MEANS AND OTHER MAJOR SYSTEM COMPONENTS.
- 6. EXISTING SERVICES: DO NOT INTERRUPT EXISTING SERVICES WITHOUT WRITTEN PERMISSION OF THE OWNER.
- 7. EQUIPMENT: CONNECT ELECTRICALLY OPERATED EQUIPMENT
- 8. RECORD DRAWINGS: MAINTAIN A RECORD OF ALL CHANGES & SUBSTITUTIONS BETWEEN WORK AS SPECIFIED AND INSTALLED. RECORD CHANGES ON A CLEAN SET OF CONTRACT DOCUMENTS WHICH SHALL BE TURNED OVER TO THE CONSTRUCTION MANAGER UPON COMPLETION OF THE
- 9. IDENTIFICATION: IDENTIFY SERVICE DISCONNECTING MEANS WITH PERMANENT NAMEPLATE.
- 10. GUARANTEE/WARRANTY: GUARANTEE INSTALLATION TO BE FREE OF DEFECTS, SHORTS, GROUNDS, ETC., FOR A PERIOD OF ONE YEAR. FURNISH WARRANTY SO THE DEFECTIVE MATERIAL AND/OR WORKMANSHIP WILL BE REPAIRED IMMEDIATELY UPON NOTIFICATION AT NO COST TO THE OWNER
- 11. CUTTING AND PATCHING: PROVIDE CUTTING REQUIRED TO DO THE WORK. DO NOT CUT MAJOR STRUCTURAL ELEMENTS WITHOUT APPROVAL. PATCHING SHALL BE OF QUALITY EQUAL TO AND OF MATCHING APPEARANCE WITH EXISTING CONSTRUCTION.
- 12. DITCHING AND BACKFILL: PROVIDE FOR ALL UNDERGROUND INSTALLED CONDUIT AND/OR CABLES.
- 13. RACEWAYS: UNDERGROUND CONDUIT SHALL BE SCHEDULE 40 PVC CONDUIT (MEET NEMA TC2 1990). EXPOSED CONDUIT SHALL BE RIGID GALVANIZED STEEL CONDUIT BEFORE RISING ABOVE GRADE. PLUG AND CAP EACH END OF SPARE AND EMPTY CONDUITS AND PROVIDE TWO SEPARATE PULL STRINGS - 200 LB. TEST POLYETHYLENE CORD. ALL CONDUIT BENDS SHALL BE A MINIMUM OF 24" RADIUS. RGS CONDUITS, WHEN SPECIFIED, SHALL MEET UL-6 FOR GALVANIZED STEEL. ALL FITTINGS SHALL BE SUITABLE FOR USE WITH THREADED RIGID CONDUIT.
- 14. SUPPORTS: AS REQUIRED BY THE NEC.
- 15. CONDUCTORS: USE 98% CONDUCTIVITY COPPER WITH TYPE XHHW-2 INSULATION, 600 VOLT, COLOR CODED. USE SOLID CONDUCTORS FOR WIRE UP TO AND INCLUDING NO. 8 AWG. USE STRANDED CONDUCTORS FOR WIRE ABOVE NO. 8 AWG.
- 16. CONNECTORS FOR POWER CONDUCTORS: USE PRESSURE TYPE INSULATED TWIST-ON CONNECTORS FOR #10 AWG AND SMALLER. USE SOLDERLESS MECHANICAL TERMINAL LUGS FOR #8 AWG AND LARGER.
- 17. SERVICE: 240/120V, SINGLE PHASE, 3 WIRE CONNECTION AVAILABLE FROM UTILITY COMPANY. COORDINATE AND PAY ALL FEES.
- 18. TELEPHONE SERVICE: PROVIDE EMPTY CONDUITS WITH PULL WIRES AS INDICATED ON DRAWINGS.
- 19. UTILITY FRAME METER CENTER: (AS REQUIRED) PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. THE ELECTRICAL DESIGN ON THESE DRAWINGS IS BASED ON A METER CENTER CONFIGURED AS FOLLOWS:
  - A. A NEMA 3R ENCLOSURE, MOUNTED ON THE FRONT SIDE OF AN EQUIPMENT FRAME INCORPORATING 120/240V, 200A METER SOCKETS AND CIRCUIT BREAKER HOUSINGS. EACH METER/CIRCUIT BREAKER COMBINATION SHALL PROVIDE SERVICE TO ONE (1) CARRIER (OR TOWER LIGHTING AS REQUIRED). METERS ARE TO BE PROVIDED BY LOCAL POWER COMPANY.
  - TOWERS REQUIRING FAA LIGHTING SHALL BE ALLOCATED ONE METER SOCKET AND CIRCUIT BREAKER HOUSING IN THE METER BANK. CIRCUIT BREAKER TO BE SIZED AS REQUIRED FOR TOWER LIGHTING EQUIPMENT. METER IS TO BE PROVIDED BY LOCAL POWER COMPANY.
- 20. UTILITY FRAME TELCO CABINET (AS REQUIRED): PROVIDED BY OWNER, INSTALLED BY CONTRACTOR. THE ELECTRICAL DESIGN ON THESE DRAWINGS IS BASED ON A TELCO CABINET CONFIGURED AS FOLLOWS
  - A. A NEMA 3R ENCLOSURE SHALL INCLUDE A 3/4" THICK PLYWOOD BACKBOARD SIZED TO FIT CABINET. A PREWIRED 20A, 120V, GFCI DUPLEX RECEPTACLE, SURGE PROTECTORS, AND A GROUND BAR. TELCO CABINET SHALL BE MOUNTED TO THE UTILITY SERVICE FRAME.
  - B. THE TELEPHONE CABINET SHALL ACCOMMODATE ALL TELEPHONE LINES (PROPOSED AND FUTURE) AND CONNECTIONS FOR THEM.
- 21. PPC CABINET: PPC CABINET SHALL BE MOUNTED TO THE EQUIPMENT SLED SERVICE FRAME. THE ENCLOSURE DESIGN ON THESE DRAWINGS IS BASED ON A NORTHERN TECHNOLOGIES PPC CABINET CONFIGURED AS FOLLOWS:
  - A. PPC CABINET SHALL BE NEMA 3R RATED AND HAVE A DOOR TO ALLOW ACCESS TO INTERNAL COMPONENTS.
  - B. THE PPC ENCLOSURE SHALL INCLUDE A 120/240V, 1 PHASE, 200A MAIN BREAKER ELECTRICAL PANEL WITH SURGE PROTECTION AND WITH CIRCUIT BREAKERS AS REQUIRED FOR SLED ELECTRICAL LOADS. SURGE PROTECTION, AN INTERIOR 20A/120V DUPLEX RECEPTACLE, AND EXTERIOR WEATHERPROOF 20A/120V DUPLEX RECEPTACLE SHALL ALSO BE INCLUDED.
  - C. PROVIDE A GROUND WIRE SIZED PER NEC IN ALL CIRCUITS OVER 20 AMPS AND IN ALL CIRCUIT RUNS IN PVC.
  - D. PPC ENCLOSURE SHALL INCLUDE A 3/4" THICK PLYWOOD BACKBOARD SIZED TO FIT CABINET AND SHALL ACCOMMODATE ALL TELEPHONE LINES (PROPOSED AND FUTURE) AND CONNECTIONS FOR THEM. IT SHALL ALSO INCLUDE 2 TELCO GROUND BARS AND PROVIDE MOUNTING SPACE FOR ALARM EQUIPMENT.

THE CONTRACTOR SHALL VISIT THE SITE BEFORE BIDDING ON THE WORK CONTAINED WITHIN THIS DESIGN PACKAGE. DISCREPANCIES AND OMISSIONS SHALL BE BROUGHT TO THE ENGINEER'S ATTENTION PRIOR TO BIDDING.

### GENERAL GROUNDING NOTES:

- 1. SITE GROUNDING SHALL COMPLY WITH T-MOBILE GROUNDING STANDARDS, LATEST EDITION, AND COMPLY WITH T-MOBILE GROUNDING CHECKLIST, LATEST VERSION. WHEN NATIONAL AND LOCAL GROUNDING CODES ARE MORE STRINGENT THEY SHALL GOVERN.
- 2. GROUND RODS:
  - A. 5/8" x 10' LONG COPPER CLAD STEEL
  - STANDARD SPACING: 10
  - C. TOP SHALL BE A MINIMUM OF 2'-6" BELOW BASE OF GRAVEL
- GROUND CONDUCTORS:
  - #2 BARE TINNED SOLID COPPER UNLESS INDICATED OTHERWISE
- WHEN DIRECTION OF CONDUCTOR CHANGES, IT SHALL BE DONE GRADUALLY
- ALL GROUNDING CONDUCTORS SHALL RUN THROUGH PVC SLEEVES WHEREVER CONDUCTORS RUN THROUGH CONCRETE SLABS.
- GROUND RINGS SHALL BE BURIED A MINIMUM OF 2'-6" BELOW BASE OF GRAVEL. GROUND RINGS SHALL BE LOCATED A MINIMUM OF 2'-0" FROM OUTSIDE EDGE OF CABINETS, TOWER FOUNDATION, AND OTHER SITE OBJECTS.
- GROUND CONNECTIONS:
  - A. ALL CONNECTIONS SHALL BE EXOTHERMIC (CADWELD OR EQUIVALENT) UNLESS INDICATED OTHERWISE
  - ALL MATERIALS USED SHALL BE INSTALLED PER MANUFACTURER'S RECOMMENDATIONS AND INSTRUCTIONS
  - CONNECTIONS AT GROUND BARS AND SERVICE DISCONNECTING MEANS SHALL CONSIST OF LUGS CADWELDED TO GROUND CONDUCTORS UNLESS INDICATED OTHERWISE. LUGS SHALL BE ATTACHED TO GROUND BARS USING STAINLESS STEEL OR HOT-DIPPED GALVANIZED STEEL BOLTS, NUTS, AND LOCKWASHERS.
- 5. COAXIAL TRANSMISSION LINE GROUNDING:
  - VERTICAL RUNS THAT ARE 200' OR LESS SHALL REQUIRE A GROUNDING KIT AT THE TOP AND BOTTOM OF TOWER.
- VERTICAL RUNS THAT ARE GREATER THAN 200' SHALL REQUIRE A GROUNDING KIT (IN ADDITION TO THE ABOVE) FROM THE TOP EVERY 150' TOWARDS THE GROUND UNTIL THE DISTANCE IS LESS THAN 150' FROM THE GROUND (NOT FOR MONOPOLES).
- SURGE ARRESTOR IS PROVIDED BY OTHERS AND INSTALLED BY CONTRACTOR. CONTRACTOR SHALL MAKE ALL CONNECTIONS REQUIRED FOR INSTALLATION. ALL GROUNDING KITS SHALL BE PROVIDED BY OTHERS AND INSTALLED BY CONTRACTOR.
- 6. MISCELLANEOUS ITEMS TO BE CONNECTED TO THE GROUNDING SYSTEM:
  - ANY METAL FENCE POST WITHIN 6' OF THE GROUND RING.
  - TRANSMISSION LINE ENTRANCE HATCH
  - METAL CABINET PARTS NOT GROUNDED BY THE INTERNAL GROUND RING.
  - METAL FUEL STORAGE TANKS
  - ANY SIGNIFICANT METAL OBJECT WITHIN 6' OF THE EXTERNAL GROUNDING SYSTEM OR ANY OTHER GROUNDED OBJECT. EXTERIOR ICE SHIELDS.
  - GENERATOR AND SUPPORT SKID OR BASE AND SWITCH.
- INSTALLATION AND TESTING:
  - A. CONTRACTOR SHALL NOTIFY CONSTRUCTION MANAGER IMMEDIATELY IF THERE ARE ANY DIFFICULTIES INSTALLING GROUNDING SYSTEM DUE TO FIELD CONDITIONS.
  - CONTRACTOR SHALL NOT COVER UP GROUND RING AND CONNECTIONS UNTIL AN INSPECTION HAS BEEN PERFORMED. COORDINATE INSPECTION WITH CONSTRUCTION
  - C. PROVIDE TESTING OF GROUNDING SYSTEM AS DIRECTED BY CONSTRUCTION MANAGER.
- 8. THE MAXIMUM ALLOWABLE RESISTANCE READING SHALL BE 5 OHMS TO GROUND. IF THE RESISTANCE OF THE ENTIRE GROUNDING SYSTEM AS MEASURED AT THE ARRESTOR BRACKET EXCEEDS 5.0 OHMS, THE ELECTRICAL CONTRACTOR AND OWNER'S REPRESENTATIVE SHALL BE NOTIFIED SO THAT ADDITIONAL GROUND LOCATIONS CAN
- 9. ALL EXPOSED GROUND LEADS TO GROUND RING, PLACED IN CONCRETE, SHALL BE ENCASED IN 3/4" FLEXIBLE CONDUIT, SEAL TYPE OR SIMILAR.
- 10. ALL GROUND WIRE CONNECTIONS TO EQUIPMENT GROUND RING THAT ARE RUNNING ABOVE GROUND SHALL BE RUN INSIDE SEALTIGHT FLEX CONDUIT.
- 11. ALL CONNECTIONS ABOVE GROUND EXCEPT CONNECTIONS TO GROUND BARS OR ARRESTOR BRACKET SHALL BE WITH DOUBLE LUG CONNECTIONS. CONNECTIONS TO GROUND BARS & ARRESTORS SHALL BE CADWELD.
- 12. COMPACT BACKFILL OF ALL TRENCHES FOR GROUNDING RING. SITE SOIL OR #57 STONE MAY BE USED FOR BACKFILL MATERIALS. CONTRACTOR SHALL OBTAIN APPROVAL FOR BACKFILL MATERIALS TO BE USED FROM CONSTRUCTION MANAGER.
- 13. CONTRACTOR SHALL PROVIDE S.S. FLAT & LOCK WASHERS AS REQUIRED FOR COMPLETE INSTALLATION OF GROUND LEADS AT GROUND BUS.

### **ABBREVIATIONS**

AFG ABOVE FINISHED GRADE AMP(S) AMPÈRE INTERRUPTING CAPACITY ATS AUTOMATIC TRANSFER SWITCH AWG AMERICAN WIRE GAUGE BCW BARE COPPER WIRE CONDUIT DWG DRAWING GROUND GENERATOR GROUND GPS GLOBAL POSITIONING SYSTEM **HERTZ** KWH KILOWATT HOUR MIN MINIMUM NTS NOT TO SCALE

POLF

PCS PERSONAL COMMUNICATION SYSTEM PPC POWER/PROTECTION CABINET PVC POLYVINYL CHLORIDE

REP REPRESENTATIVE RGS RIGID GALVANIZED STEEL RACFWAY

SCHEDULE SPE SERVICE PROTECTION ENCLOSURE TBD TO BE DETERMINED

TYP TYPICAL UG UNDERGROUND VOLT(S)

### SYMBOLS LEGEND

METER

DISCONNECT SWITCH

 EXPOSED RACEWAY ---- UNDERGROUND RACEWAY

· CONDUIT TURNED TOWARD VIEWER 5/8"ø x 10'-0" GROUND ROD

GROUND ROD TEST WELL

GROUNDING CONDUCTOR

GROUND CONNECTION

GROUND BAR

compass 5449 Bells Ferry Road Acworth, Georgia 30102 770-701-2500 Fax 770-701-2501

WALTER MATHEWS PRATHER, P.E.

GEORGIA P.E. No. 19114

	ESIGN REVISI	ons <del></del>	
			-
1	08/27/12	ISSUED FOR CONSTRUCTION	В
0	07/02/12	ISSUED FOR CONSTRUCTION	TI∿



S

9AT0289B

WILLEO CREEK 2

APPROVED BY: DESIGNED BY: T. MERCHANT PROJECT NO: 100396

GENERAL ELECTRICAL NOTES AND SYMBOLS

compass 5449 Bells Ferry Road Acworth, Georgia 30102 770-701-2500 Fax 770-701-2501 WALTER MATHEWS PRATHER, P.E. GEORGIA P.E. No. 19114 08/27/12 0 07/02/12 CONSTRUCTION NO. DATE NOT VALID WITHOUT SI 1. MOLH 9114~ PROFESSIONAL VGINEER Ì 9AT0289B WILLEO CREEK 2

DESIGNED BY:

PROJECT NO:

T. MERCHANT

100396 05/30/12

PLUMBING DIAGRAM

E-2